



Fiberglass Door Slab Construction Features & Materials

Door Slab Components:

- FJ Primed Pine Door Stiles and Rails
- Wooden Lock Block
- Poly-urethane insulated foam core
- Smooth – Primed Fiberglass door skins
- Standard Vinyl 4 fin Door sweeps

Features:

- Standard 3/0 Slab Measurements: 1-3/4" Slab Thickness, 79" Slab Height, 35.75" Slab Width
- Mortised Hinges
- Non-Certified, Tested, or Rated Door Slab
- Lites include 1" Insulated Glass

Warranty

Door Worx warrants all Fiberglass exterior doors for use in normal conditions against defects in workmanship and materials for a period of one year from the date of delivery. Door Worx will, at its option, either repair or replace any defective doors, and will have no liability or obligation for any damages of any kind beyond such repair or replacement.

This warranty is subject to the following provisions:

- (a) Appropriate product application and hardware selection
- (b) Appropriate job site storage outside of the weather
- (c) Proper installation of the door and frame in accordance with industry standards
- (d) All material is required to receive a coating of finish paint within 30 days of delivery. This includes all 6 surfaces of the door
- (e) Warranty shall not apply to products which, in the opinion of Door Worx have been modified, repaired, altered in any way without the express written consent of the Company.