

Here are just a few of the ways Meade's can customize your build:

- Extended Jambs (\$150+)
 - Dutch Door (\$300+)
 - Doggy Door in door (\$150+)
 - T-astragal on interior double (+\$300+)
 - Transoms (\$250+)
 - Specialized heights (\$150+)
 - Specialized widths (\$150+)
 - Triples, Quads or Interior Sidelites (\$TBD)
 - Special Configurations (\$TBD)
 - Don't see it? – just ask!
-

Please note that it is **best practice** to have the installer of the door approve the size and specifications you are purchasing. Even if a salesperson works with you in store or virtually, Meade's cannot be responsible for any measures or builds "fitting" unless we have been on jobsite and you have purchased a measure from Meade's. We will build to standard measurements or the measurements given for a custom order.

Interior Pre-hung Specifications:

By selecting the pre-hanging option for your interior door slab, you will receive a door hinged, prepped for handle (unless double French door) and assembled in a frame (also called the door "jamb").

Each pre-hung door unit includes:

- 4-9/16" wide jambs
 - 3 Oil Rubbed Bronze hinges on doors less than 84" tall and 4 ORB Hinges on doors greater than 84" tall
 - Pre-drilled door for handle (no drill on either door for doubles)
 - We will pre-drill the door for a handle with 2-3/8"
 - Bore diameter: 2-1/8"
 - Jamb will not be prepped for strike plates or bored for plungers. This will need to be done on site by installer.
 - NO interior door trim will be included on interior doors
 - Double doors are built to be standard ball catch closure. So they are not prepped for handles as dummy handles are standard. Slabs and Jambs are not prepped for ball catch due to those usually being installed during door installation.
 - Interior doubles do not include t-astragals unless it is a quoted custom build.
-

Standard Interior Pre-Hung Measurements:

- Outside Jamb to Outside Jamb Width: Door slab selected width + 1 11/16"
- Outside Jamb to Outside Jamb Height: Door slab selected height + 1 7/8"
- Rough Opening Width: Door slab selected width + 2"
- Rough Opening Height: Door slab selected + 2.5"

Selecting A Door Handing Option:

DOOR HANDING / SWING CHART

